## CLAIMS

An acoustic telemetry apparatus for communicating digital data from a down-hole location through a borehole to the surface comprising:

an acoustic channel terminated at a down-hole end by a reflecting terminal;

an acoustic wave generator located at the surface and providing an acoustic wave carrier signal within said acoustic channel;

10

15

20

a modulator located at said down-hole location and adapted to modulate amplitude and/or phase of said carrier wave in response to a digital signal; and

one or more sensors located at the surface adapted to detect amplitude and/or phase related information of acoustic waves traveling within said acoustic channel.

- 2. The apparatus of claim 1 wherein the modulator modulates the reflection properties of reflecting terminal.
- 3. The apparatus of claim 1 wherein the modulator and the reflecting terminal form a variable phase shifting reflector for the carrier wave.
- 25 4. The apparatus of claim 2 wherein the modulator modulates the reflection properties of the reflecting terminal in discrete steps.
- 5. The apparatus of claim 4 wherein the modulator
  30 switches between a first state that causes the phase of an
  acoustic wave reflected at said terminal to invert and a
  second state that maintains the original phase of the

incident wave.

10

25

6. The apparatus of claim 1 wherein the acoustic channel is a column of liquid extending from the surface to a down-hole location.

- 7. The apparatus of claim 6 wherein the acoustic channel is formed by filling an annular volume in the borehole with a liquid.
- 8. The apparatus of claim 6 wherein the acoustic channel is formed by filling a tubing string suspended in the borehole with a liquid.
- 15 9. The apparatus of claim 6 wherein the column of liquid has a viscosity of less than  $3\times10^{-3}$  NS/m<sup>2</sup>.
- 10. The apparatus of claim 1 wherein the modulator is a resonator located in the vicinity of the reflecting terminal point.
  - 11. The apparatus of claim 10 wherein the resonator comprises a liquid filled volume enclosed in a housing having a tubular opening to the reflecting terminal.
  - 12. The apparatus of claim 11 wherein the resonator has two or more tubular openings to the reflecting terminal.
- 13. The apparatus of claim 11 wherein the acoustic 30 wave generator is adapted to simultaneously generate acoustic waves at different frequencies.

1

14. The apparatus of claim 1 further comprising an acoustic receiver in a down-hole location adapted to receive acoustic channel in a down-hole location.

- 5 15. The apparatus of claim 1 wherein the digital data is encoded digital data.
- 16. The apparatus of claim 1 wherein the sensors are connected to a decoding unit adapted to convert detected

  10 amplitude and/or phase related information into a digital signal.
- 17. The apparatus of claim 1 wherein the sensors are connected to a signal processing unit adapted to filter the carrier wave signal from detected information.
  - 18. The apparatus of claim 1 wherein the modulator comprises a piezoelectric actuator.
- 20 19. The apparatus of claim 1 comprising a down-hole power generator adapted to convert acoustic energy from an acoustic wave signal generated at the surface.
- 20. Use of the apparatus of claim 1 in a well stimulation operation.
  - 21. A method of communicating digital data from a down-hole location through a borehole to the surface comprising the steps of:
- establishing an acoustic channel through said borehole and terminating said acoustic channel at a downhole end by a reflecting terminal;

generating from the surface an acoustic wave carrier signal within said acoustic channel;

A PARTY NO.

modulating amplitude and/or phase of said carrier wave in response to a digital signal; and

detecting at the surface amplitude and/or phase related information of acoustic waves traveling within said acoustic channel.

- 22. The method of claim 21 wherein the step of modulating amplitude and/or phase of the carrier wave comprises the step of changing the reflecting properties of the reflecting terminal.
- 23. The method of claim 22 wherein the reflecting properties of the reflecting terminal are changed in discrete steps.
- 24. The method of claim 21 further comprising the step of placing a Helmholtz resonator in proximity to the 20 reflecting terminal.
  - 25. The method of claim 21 further comprising the steps of

performing measurements of down-hole parameters,
encoding said measurements into a bitstream; and
controlling the reflecting properties of the
reflecting terminal in response to said encoded bitstream.

26. The method of claim 21 further comprising the 30 step of

selecting the frequency of the carrier wave such that it is close to the resonance frequency of a resonator

used to modulate said carrier wave.

27. The method of claim 21 further comprising the steps of

5 scanning through a range of possible carrier frequencies;

monitoring at the surface reflected and modulated wave signal;

selecting the frequency of the carrier wave such that the detection of said reflected and modulated wave signal is optimized; and

commencing the communication of down-hole measurements.

28. A method of stimulating a wellbore comprising the steps of

performing operations designed to improve the production of said wellbore while simultaneously establishing an acoustic channel through said borehole and terminating said acoustic channel at a down-hole end by a reflecting terminal;

generating from the surface an acoustic wave carrier signal through within said acoustic channel;

modulating amplitude and/or phase of said carrier wave in response to a digital signal; and

detecting at the surface amplitude and/or phase related information of acoustic waves traveling within said acoustic channel.

20

25

## **AMENDED CLAIMS**

[Received by the International Bureau on 30 August 2004 (30.08.04): new claims 29-33 added; original claims 1-28 unchanged; (1 page)]

- 29. A down-hole power generation system adapted to convert acoustic energy from an acoustic wave signal generated at the surface and transmitted down the annulus of a wellbore, the system comprising:
- a surface power source adapted to send an acoustic wave down the annulus;
  - a down-hole generator located within the annulus and comprising an electro-acoustic transducer adapted to convert the energy of the acoustic wave into electrical energy; and

an energy storing capacitor adapted to store the electrical energy and provide power to down-hole devices.

- 30. The down-hole power generation system of claim
  15 29, wherein the surface power source is an electro-dynamic type actuator.
- 31. The down-hole power generation system of claim 29, wherein the surface power source is a piezoelectric 20 bender type actuator.
  - 32. The down-hole power generation system of claim 29, wherein the surface power source is a high stroke rate and low volume piston pump.
  - 33. The down-hole power generation system of claim 29, wherein the electro-acoustic transducer comprises a piezoelectric stack.

25

10